

Ref code	Capacity	Base Size	Height
PHRC1000	1000Lts	1200mm x 1100mm	1670mm

PHRC IBC CONTAINER

- Long life stainless steel IBC in galvanised frame
- UN certified for packaging groups II & III
- Stack 2 high when full
- 4 way fork or pallet truck handling and top lift facility
- Tare weight: 250kgs e
- DN400 manlid
- Agitation device available
- Maximum operating pressure 0.65 bar



Tank Shell	2/2.5mm 1.4301 stainless steel with III d (2R DIN EN 10088) finish suitable for food stuffs or chemical use.
Capacity	1000 Litres
Base Frame	Hot galvanised according to DIN EN ISO 1461
Manlid	DN400 c/w screwed cover and 6 eye bolts
Sockets	2 off mounted on the tank top. 1 X 1" sockets with stainless steel overpressure valve (0.65 bar), 1 x Nitrogen vent diameter 6.5mm.
Safety Valve	1" stainless steel overpressure valve (0.65 bar)
Outlet	Spherical discharge with flange and 2" ball valve with closure cap - discharged to the long side.
Markings	UN certification plate and manufacturer's plate.
Labelling	As required.
Handling	4 way fork truck entry and top lift facility.
Stacking	2 high when full. 5 high when empty.
Certification	GGVSEB / GGVSea / ADR /RID packaging group II and III.
Max Density	1.83 kg/litre
Equipment	Valve protection – grounding – IBC plate